

McKissick® Oilfield Servicing Blocks

SELBY ENGINEERING & LIFTING SAFETY LTD.
 Lifting Equipment and Height Safety Specialists
 www.liftingsafety.co.uk sales@liftingsafety.co.uk
 Tel: +44 (0) 1977 684 600 Fax: +44 (0) 1977 685 300

SEE APPLICATION AND WARNING INFORMATION
 Para Español: www.thecrosbygroup.com On Pages 342-349

WELL LOGGER'S BLOCKS



475



477



476

Floor Blocks & Top Blocks

- Alloy aluminum housing for maximum strength and minimum weight.
- Conductor cable ONLY is recommended for use with Well Logger's Blocks.
- For use in high speed well logging, perforating, etc.
- Extra large double row, pre-adjusted sealed tapered bearing.
- Quick opening pin for fast string-up, light weight for easy handling.

FLOOR BLOCKS						
Sheave Diameter (in.)	Block No.	Floor Block Stock No.	Working Load Limit (Tons)*	Conductor Cable Size (in.)†	Weight Each (lbs.)	Connection
7	475	180020	1-1/2	3/16	10	Swivel Hanger
10	473	180128	1-1/2	3/16	11	Swivel Hanger
10	475	180253	2-1/2	5/16	21	Swivel Hanger
12	475	180440	2-1/2	5/16	24	Swivel Hanger
14	475	180618	2-1/2	5/16	43	Swivel Hanger
14	477	169784	6	1/4	58	Swivel Clevis
20	477	191072	6	1/4	70	Swivel Clevis
24	477	191107	10	5/16	130	Swivel Clevis

* Ultimate Load is 4 times the Working Load Limit.
 † Other cable sizes available upon request.

TOP BLOCKS						
Sheave Diameter (in.)	Block No.	Top Block Stock No.	Working Load Limit (Tons)*	Conductor Cable Size (in.)	Weight Each (lbs.)	Connection
7	476	180075	2-1/2	5/16	10	Stinger Pin
10	474	180173	2-1/2	3/16	10	Stinger Pin
10	476	180333	4	5/16	21	Stinger Pin
12	476	180529	4	5/16	24	Stinger Pin
14	476	180707	4	5/16	43	Stinger Pin

* Ultimate Load is 4 times the Working Load Limit.