



ME06 SHOCK ABSORBING LANYARD - 2M - ML04+ML00

Product use

2 m webbing shock absorbing lanyard equipped with a 63mm opening scaffold hook ML04 and a screwgate karabiner ML00

Technical description

Webbing

Yellow webbing
 Width : 23mm
 Raw material: Polyester
 Breaking strength: > 3000 daN

Energy Absorber

Raw material: Polyester/ Polyamide 30mm
 Standard: EN 355
 Breaking strength for linked element: > 3200 daN
 Breaking strength for unlinked element: > 1500 daN

Screwgate Karabiner ML00

Raw material: Galvanised steel
 18mm Opening
 Standard: EN 362
 Breaking strength: > 2200 daN

Automatic snap hook ML04

Raw material: White chromate steel
 Standard: EN 362
 Opening : 63 mm
 Breaking strength: > 2000 daN

Weight : 0.930 kg

Tests

Breaking strength: > 15 KN

Temperature: -30°C to +50°C

Technical specifications and standard

European directive :
 89/686/CEE

Norms :
 EN355

EC type attestation :
 0082/490/160/04/00/0144

Quality Assurance
 AFAQ: ISO 9001 : Version 2000

Certification number :
 0333 AFAQ/CTH

Marking :
 MILLER



Additional information

click address to go to...

ME06 SHOCK ABSORBING LANYARD - 2M - ML04+ML00

The supplier or its legal representative supplier settled in the European community :

MILLER

declares that the new Individual Protection Equipment described hereafter :

Designation :

ME06 Shock Absorbing Lanyard - 2m - ML04+ML00

Article code :

10 045 79

is in conformity with Directive dispositions 89/686/CEE.

This PPE has been the object of the EC attestation type :

0082/490/160/04/00/0144

delivered by :

**APAVE Lyonnaise
177 route de Saint-Bel
69811
TASSIN CEDEX
France**

Identified by the number :

0082

Made on the : **05/08/2004**

at : **Vierzon**

Division : **Fall Protection**

By : **Frederic GUICHARD**

[click address to go to...](#)